(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 28 July 2005 (28.07.2005)

PCT

(10) International Publication Number WO 2005/068847 A1

(51) International Patent Classification7: B63J 5/00 F04D 29/58,

(21) International Application Number:

r: PCT/EP2005/000279

(22) International Filing Date: 13 January 2005 (13.01.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0400986.6

16 January 2004 (16.01.2004) GE

- (71) Applicant (for all designated States except US): CRYOSTAR-FRANCE S.A. [FR/FR]; Boite Postale 48, Zone Industrielle, F-68220 Hesingue (FR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): POZIVIL, Josef [CH/FR]; c/o Cryostar France S.A., Boite Postale 48, Zone Industrielle, F-68220 Hesingue (FR). GERSTENDO-ERFER, Helmut [AT/CH]; Bodenacker 175, CH-5016 Ober-Erlinsbach (CH).


- (74) Agent: WICKHAM, Michael: The BOC Group plc, Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: COMPRESSOR



(57) Abstract: A rotary liquefied natural gas boil-off compressor 10 has a series of compression stages 12, 14, 16 and 18. A gas passage 8 passes through the series of compression stages. The gas passage 8 extends through and is in heat exchange relationship with cooling means 26, 28 and 30 in the form of indirect heat exchangers. Each of the heat exchangers 26, 28 and 30 is cooled by LNG supplied from a pipeline 36. Flow control valves 50, 52 and 54 are provided for controlling the flow of LNG to the heat exchangers 26, 28 and 30 respectively. The valves 50, 52 and 54 are controlled in response to temperature sensors 60, 62 and 64, respectively, so as to maintain the inlet temperature of each of the compression stages 14, 16 and 18 at a chosen sub-ambient temperature or between chosen sub-ambient temperature limits.